



M12, 2NOS. EARTHING SCREW
ONE ON EACH SIDE.

**SHAFT EXTENSION
DETAILS**

NOTE:-

1. MOTOR CONFORMS TO IS:325
2. DEGREE OF PROTECTION: IP:55
3. TOLERANCE ON "D" : m6.
4. PROTECTED CENTER HOLE "M24X50" DEEP FOR 4P & ABOVE, "M20X40" DEEP FOR 2P AS PER IS:2540 AT SHAFT EXTENSION.
5. TERMINAL BOX CAN BE ROTATED THROUGH 360° IN STEPS OF 90°
6. 3 PAIRS OF MOUNTING HOLES ARE PROVIDED ON MOTOR AT NDE SIDE. CUSTOMER CAN CHOOSE ANY ONE PAIR OF MOUNTING HOLES FOR FOUNDATION

SCX355X	6 & 8	610	125	710	700	415	500	560	630	150	300	780	254	100	210	28	106	16	10	355	50	875	28	1820
SCX355X	4	610	125	710	700	415	500	560	630	150	300	780	254	100	210	28	106	16	10	355	50	875	28	1670
SCX355X	2	610	125	710	700	415	500	560	630	150	300	780	254	80	170	22	85	14	9	355	50	875	28	1630
FRAME	POLE	A	AA	AB	AD	AD'	B	B'	B''	BA	BA'	BB	C	D	E	F	GA	GD	GE	H	HA	HD	K	L

CUSTOMER / O/A No.

USED ON / TYPE
SCX355X

SCALE
NTS



DRAWN	Sd/Spf	25/05/06
CHECKED	Sd/RSR	25/05/06
APPROVED	Sd/BVS	31/05/06

SHEET NO. ONE OF ONE
31102706



REV.	ZONE	BRIEF RECORD	DRAWING No.	FROM DT.	DATE
PP & MM					
MKT.G.ACM					
ALL INFORMATION CONTAINED IN THIS DOCUMENT IS CONFIDENTIAL AND THE PROPERTY OF KIRLOSKAR ELECTRIC CO. LTD. REPRODUCTION OF THESE IN ANY FORM IS TO BE DONE WITH THE SPECIFIC PERMISSION OF THE COMPANY.					
PRINTS ISSUED TO					

DIMENSIONAL DRAWING

KIRLOSKAR ELECTRIC COMPANY LTD. BANGALORE - 560055 (INDIA)